

Nedap Flux

# Gateway

## Quick guide

Public

528002 Version: December 2024



## 1. Copyright-Disclaimer

Copyright © Nedap N.V., Parallelweg 2, NL-7141 DC Groenlo, The Netherlands. This document is property of Nedap N.V. and the content is not to be reproduced in any way, in whole or in part, without the prior written consent of Nedap N.V. Nedap N.V. makes no representations or warranties whether express or implied as to the accuracy, correctness, completeness of this document. If this document is part of the installation manual, the installation manual will be leading. You use the products at your own risk. Nedap N.V. reserves the right to make changes to this document and/or the products described. Please consult the portal ([www.nedapflux.com/nl/hardware-en](http://www.nedapflux.com/nl/hardware-en)), for any changes or notification.

## 2. Disposal of equipment



The products will be disposed of by the end-user and discharge Nedap for any liability or responsibility thereof.

## 3. Compliancy

Hereby, Nedap N.V. declares that this equipment is in compliance for CE with directives 2014/30/EU (EMC Directive) and 2011/65/EU (RoHS). And for UKCA with SI 2016/1091 (UK EMC Regulations 2016) and UK RoHS Regulations 2012.

Full text of declarations of conformity is available at [www.nedapflux.com/nl/hardware-en](http://www.nedapflux.com/nl/hardware-en), where, if applicable, also REACH information can be found.

## 4. Technical information

### General

Model FLUX GATEWAY  
Product code 9951650

### Communication

Wireless 868MHz  
900/1800 MHz GSM

Optical Status LEDs

### Power

100-240VAC 0.6-0.3A 50-60Hz  
Adapter included

### Mechanical

Dimensions (LxBxH) 211 x 91 x 43 mm

Weight ± 440 gr

Operating temperature 0 °C – 40 °C

Storage temperature 0 °C – 40 °C

Relative humidity 0 – 93% (non condensing)

Usage Inside (IP20)

## 5. Installation and use

See installation manual 5280003 at [www.nedapflux.com/nl/hardware-en](http://www.nedapflux.com/nl/hardware-en)

Note: The 4 digit number shown on the equipment is used during installation.

Nedap N.V.  
Parallelweg 2  
7141 DC Groenlo  
The Netherlands

